


EXP-20EZ

REVISION: K
ECO NO.: 2589-2
BY: M. LLOYD
DATE: 03-28-08

COXREELS SERIES EZ-T



ITEM	PART	DESCRIPTION	QTY
20	1620	BOLT: ½"x1½" SHOULDER	1
21	274-1-SS	SPRING: LOCK DOG	1
22	1794	AXLE: 1"	1
23	437	WASHER: 3/8" LOCK	1
24	184	NUT: 3/8-16 JAM	1
25	1953	BOLT: 1/4-20 x 1 1/2" CARRIAGE	3
26	125	NUT: 1/4-20 KEPS	7
27	245	SCREW: #10-32 x 3/8" TRUSS HEAD	2
28	438	WASHER: 5/8" LOCK	1
29	3584	NUT: 5/8-11 HEX	1
30	312	BOLT: 5/16-18 X 3/4" HEX	12
31	130	NUT: #10-32 KEPS	2

ITEM	PART	DESCRIPTION	QTY
32	111	NUT: 5/16-18 NYLOCK HEX	12
33	111-1	NUT: 5/16-18 NYLOCK HEX (LOW PROFILE)	4
34	10235-SS	STUD: 3/8-16 X 1" SS	1
35	1924	RING: LOCKING	1
36	1755-1	WASHER: SPACER	1
37	1753	RING: #5160-75 RETAINING	1
38	10220-75	BOLT: 5/16"-18 x 3/4" CARRIAGE	4
39	6440-SS	WASHER: SPACER SS	1
40	6441-1	WASHER: SPACER	1
41	10925-5B	LABEL: PRODUCT ID.	1
42	10950	LABEL: EZ-COIL ARM	2
43	10937	LABEL: EZ-COIL PRODUCT	1
44	10937-1	LABEL: EZ-COIL PATENT NO.	1

ITEM NUMBER

MODEL	ITEM NUMBER																			
	1	2	3	4	5	7	* 8			* 9	10	11	12	13	14	15	* 16	17	18	19
	SPRING	DRUM	DRUM	BASE	ARM	SWIVEL	HOSE (STD)	HOSE (-OG)	HOSE (-RH)	GUARD	ARM	EZ-COIL	CAM	CLAMP (2)	ELBOW	BRKT.	BALL ST	SUPP.	R.RING	SPACER
EZ-TSH-375	698-1	1705	1704	1786	1733	433	5153-75	5101-75	5045-75	237-1	1825	7474-8-R	640-1-SS	381	-	1829-1	131-3	1741	1754	7511
EZ-TSH-3100	698-2	1705	1704	1786	1733	433	5153-100	5101-100	5045-100	237-1	1825	7474-8-R	640-1-SS	381	-	1829-1	131-3	1741	1754	7511
EZ-TBLL-3100	698-2	1705	1704	1786	1733	433-FG-SS	-	-	-	-	1825	7474-8-R	640-1-SS	381	-	1829-1	-	1741	1754	7511
EZ-TSH-450	691-3	1703	1702	1784	1732	434	5154-50	5131-50	5066-50	398-1	1827	7474-6-R	640-1-SS	382	-	1829-1	131-4	1740	1754	7511
EZ-TSH-475	692-2	1705	1704	1786	1733	434	5154-75	5131-75	5066-75	398-1	1825	7474-8-R	640-1-SS	382	-	1829-1	131-4	1741	1754	-
EZ-TSH-4100	656	1705	1704	1786	1733	434	5154-100	5131-100	5066-100	398-1	1825	7474-10-R	640-1-SS	382	-	1829-1	131-4	1741	1754	-
EZ-TSH-535	695-1	1705	1704	1786	1733	426	5155-35	5163-35	5091-35	398-1	1825	7474-8-R	640-1-SS	384	385	8740	430	1712	516	7511
EZ-TSH-550	692-1	1705	1704	1786	1733	426	5155-50	5163-50	5091-50	398-1	1825	7474-8-R	640-1-SS	384	385	8740	430	1712	516	-
EZ-TSHF-550	692-1	1705-1	1704	1786	1733	426	5097-50	-	-	398-1	1825	7474-8-R	640-1-BR	384	385	8740	430	1712	516	-

ITEM NUMBER

MODEL	ITEM NUMBER																		
	1	2	3	4	5	7	* 8												
	SPRING	DRUM	DRUM	BASE	ARM	SWIVEL	HOSE (STD)	* 9	10	11	12	13	14	15	* 16	17	18	19	
								GUARD	ARM	EZ-COIL	CAM	CLAMP (2)	ELBOW	BRKT.	BALL ST	SUPP.	R.RING	SPACER	
EZ-TMP-350	699-1	1703	1702	1784	1732	433	5224-50	237-1	1827	7474-8-R	640-1-SS	381	-	1829-1	131-3	1740	1754	7511	
EZ-TMP-375	656	1705	1704	1786	1733	433	5224-75	237-1	1825	7474-10-R	640-1-SS	381	-	1829-1	131-3	1741	1754	-	
EZ-TMP-450	649	1703	1702	1784	1732	434	5256-50	398-1	1827	7474-10-R	640-1-SS	383	-	1829-1	131-4	1740	1754	-	
EZ-TMP-475	656	1705	1704	1786	1733	434	5256-75	398-1	1825	7474-10-R	640-1-SS	383	-	1829-1	131-4	1741	1754	-	
EZ-TMP-550	654	1705	1704	1786	1733	426	5290-50	398-1	1825	7474-10-R	640-1-SS	387	385	8740	430	1712	516	-	

ITEM NUMBER

MODEL	ITEM NUMBER																		
	1	2	3	4	5	7	* 8												
	SPRING	DRUM	DRUM	BASE	ARM	SWIVEL	HOSE (STD)	* 9	10	11	12	13	14	15	* 16	17	18	19	
								GUARD	ARM	EZ-COIL	CAM	CLAMP (2)	ELBOW	BRKT.	BALL ST	SUPP.	R.RING	SPACER	
EZ-THP-150	647	1703	1702	1784	1732	499	5304-50	237-1	1827	7474-6-R	640-1-SS	115	-	1829-1	131	1740	1754	7511	
EZ-THP-175	698-3	1705	1704	1786	1733	499	5304-75	237-1	1825	7474-8-R	640-1-SS	115	-	1829-1	131	1741	1754	7511	
EZ-THP-1100	657	1705	1704	1786	1733	499	5304-100	237-1	1825	7474-10-R	640-1-SS	115	-	1829-1	131	1741	1754	-	
EZ-THP-350	696-1	1703	1702	1784	1732	521	5336-50	237-1	1827	7474-8-R	640-1-SS	613	-	1829-1	131-3	1740	1754	-	
EZ-THP-375	656	1705	1704	1786	1733	521	5336-75	237-1	1825	7474-10-R	640-1-SS	613	-	1829-1	131-3	1741	1754	-	
EZ-TBHL-3100	657	1705	1704	1786	1733	433-FG-SS	-	-	1825	7474-10-R	640-1-SS	381	-	1829-1	-	1741	1754	-	

* ON "LESS HOSE" MODELS (EZ-TSHL-/EZ-TMPL-) EXCLUDE ITEMS #8, #9, AND #16.
 NOTE: MODELS SUPPLIED WITH "STANDARD" HOSE UNLESS SUFFIXED WITH "-OG" OR "-RH". USE HOSE NUMBERS AS NOTED ABOVE.

REEL ASSEMBLY REPORTS: R100 (LATCHOUT REMOVAL), R101 (LOCKING RING PLACEMENT), R112 (TIGHTENING AND TORQUING)

REVISION: K ECO: 2589-2 DATE: 3/28/2008 NAME: M. LLOYD